

ClothingPad Combo Technical Specifications

Product Dimensions

Product Dimensions (L x W x H):	80.3 x 110 x 97 in (204 x 279.4 x 246.4 cm)
Product Weight:	1064.1 lb (482.7 kg)
Shipping Dimensions:	92 x 42 x 28 in (233.7 x 106.7 x 71.1 cm), 414.5 lb (188 kg) 58 x 46 x 18 in (147.3 x 116.8 x 45.7 cm), 257.9 lb (117 kg) 93 x 63 x 27 in (236.2 x 160 x 68.6 cm), 650.4 lb (295 kg) 61 x 53 x 19 in (154.9 x 134.6 x 48.3 cm), 209.4 lb (95 kg) 59 x 55 x 21 in (149.9 x 139.7 x 53.3 cm), 242.5 lb (110 kg) 72 x 21 x 15 in (182.9 x 53.3 x 38.1 cm), 70.5 lb (32 kg)
Shipping Weight (Total):	1845.2 lb (837 kg)
Max Object Shooting Size:	
Top Shots:	44.5 x 26 in. (113 x 66 cm)
Side Shots:	42.5 x 49 in. (108 x 124 cm)
360 Shot:	36.6 x 36.6 x 45 in. (93 x 93 x 114 cm)
Turntable Diameter:	47.25 in. (120 cm)
Turntable Type:	Bottom-Lit, Edge-Driven
Max Object Weight:	44 lbs. (20 kg)
Assembly / Disassembly:	Planned / Documented
Mobility:	Wheels and Leveling Legs

Computer / Software Requirements

Operating System: Windows / Mac (Software Requirements Page)

Ports: 2 USB ports (for camera and system)

Power Specifications

Amps, Watts, Voltage:

Light Table:	6.2 Amps, 620 Watts, 100 to 240 Volts
Turntable:	0.2 Amps, 12 Watts, 100 to 240 Volts
Back / Top Light:	1.4 Amps, 140 Watts, 100 to 240 Volts
Total System:	7.8 Amps, 772 Watts, 100 to 240 Volts

Lighting Specifications

Adjustable LED Light Sources: Top, Back Left, Front Left, Back Right, Front Right, Bottom, Back Middle

Color Temperature: 5700K ± 200K

Color Rendering Index: CRI : Ra >97

Dimming Control: 0 - 100% in 1% increments

LED Service Life: 50,000+ Hours

Optional Diffusion Covers: Yes

Output Options

Still:

Output Format: JPG, PNG, TIFF, TIFFA, RAW, PSD, WebP, HTML, TARGA, Raw JPG

360:

Max Number of Images: Up to 1024 still frames

Output Formats:
- Still Photos
- GIF
- Photo Sequences
- Stitched Animations in HTML (Images in JPG, PNG, or WebP)

Video:

Max Video Size:	8K (camera dependent)
Video Output:	MOV, MP4
Compression:	H264, H265

Parts and Accessories

1. Cross Beam
2. 2 Fixing Plates (1 for Support Rack and 1 for Vertical Arm)
3. 2 L-Shaped Fixing Plates
4. 2 Light Support Studs
5. 4 Light Arms
6. 4 Holding Brackets
7. 2 Canopy Rods
8. Fabric Canopy
9. Vertical Base
10. Vertical Arm
11. 2 Base Covers
12. 2 L-Shaped Camera Mount Brackets
13. Horizontal Arm
14. #5, #6 and #10 Allen Keys
15. 8 M8 Allen Screws
16. 36 Sets of M8 Allen Screw with Spring and Flat Washers
17. 4 Sets of M12 Allen Screws with Spring and Flat Washers
18. 4 M6 Small White Hand Screws
19. 10 M8 White Hand Screws (8 short and 2 long)
20. #24 Wrench
21. 8 Sets of Clamp Lever with Flat Washer
22. System Power Cable (15 Amp)
23. 2 USB Cables (1 B to A and 1 B to C)
24. USB Extension Cable
25. Ortery Capture Software Box
26. Fabric Table Cover
27. Measurement Calibration Tool and 4 Plastic Caps (spare)
28. 2 Support Racks
29. 4 Light Panels
30. 4 Light Diffusion Covers
31. 4 Light Power Cables
32. Light Table
33. 2 Acrylic Table Diffusion Plates (1 spare)