

DualView 600 Technical Specifications

Product Dimensions

Product Dimensions (L x W x H):	27.4 x 33.5 x 80.7 in (69.7 x 85 x 205 cm)
Product Weight:	86 lb (39 kg)
Shipping Dimensions:	78 x 18 x 16 in (199 x 45 x 41 cm), 99.2 lb (45 kg)
Shipping Weight (Total):	99.2 lb (45 kg)
Top Arm Max Length:	21.5 in (54.6 cm)
Bottom Arm Max Length:	10 in (25.4 cm)
Assembly / Disassembly:	Planned / Documented
Mobility:	Locking Casters and Adjustable Feet

Computer / Software Requirements

Operating System:	Windows / Mac (Software Requirements Page)
Ports:	1 USB, 1 Power Receptacle and 1 Power Port on each horizontal arm
Cables:	2x 6ft Power Cords

Output Options

Still:

Output Format:	JPG, PNG, TIFF, TIFFA, RAW, PSD, WebP, HTML, TARGA, Raw JPG

360:

Max Number of Images:	Up to 1024 still frames
Output Formats:	- Still Photos - GIF - Photo Sequences - Stitched Animations in HTML (Images in JPG, PNG, or WebP)

DualView 3D:

Max Number of Images:	Up to 1024 images
Max Number of Rows:	2 rows
3D Modes:	Mode A - 2 Angle (high/low) Mode B - 2 View Variation (open/closed) Mode C - 2 Product Positions
Animation Outputs:	JPG, PNG, WebP

Video:

Max Video Size:	8K (camera dependent)
Video Output:	MOV, MP4
Compression:	H264, H265

Parts and Accessories

1. Caster rail
2. Branch caster rail
3. 4 Sets of silver screws with spring washer and flat washer
4. Hex key
5. #24 Wrench
6. Vertical arm
7. 6 Black flat head screws
8. 2 Horizontal arms (8-1 short and 8-2 long)
9. Plastic end cap (large)
10. 2 Camera mount brackets
11. 2 Plastic end caps (small)
12. 2 Black half threaded hand screws
13. 2 Tripod heads
14. 2 Spare reducer bushings
15. 2 Spare rubber gaskets
16. 2 Power cables
17. 2 Short Velcro strips
18. 6 Long Velcro strips
19. Installation Guide